

DIGIDRIVE T.L.+PSU DTL

Reference CD player-transport top loading



Mechanics has become a rare expertise in these all electronics times. Although mechanics act as the heart of the very source, improvements and research are focused on the electronic aspect only. A very small number of sophisticated mechanisms are available in the market but they all come from mass production technics not suitable for top quality music reproduction.

The Digidrive Top-Loading reference transport combine our long experience in design and physics applied to High End Audio with pure mechanism, advanced electronics, audiophile detail and all facilities to open a new dimension in musical enjoyment.

A special material as alluminium cabinet , output digital transformers and hi-quality servo drive electronics section provides a right balancing for true-genuine performance.

A genuine top loading CD-Player don't have a center disc stabilizer integrated with top cover but the disc stabilizer must be free to insert manually in center disc.

The massive one piece plexiglass solid front board, the one piece of alluminium body especially the large internal structure off brass guarantee exceptional rigidity and mechanical stability.



Open top spider draw



Rear panel of digidrive: digital output for RCA SPDIF by Pulse transformer, BNC direct output without pulse transformer and AES-EBU professional RS-422 digital output.

Switch facility: Display ON/OFF light, ground loop switch



Digidrive low noise, hi-energy power supply. Separate power supply reduce flux noise to the laser assembly and reduce hum effect to the chassis

DIGIDRIVE T.L.+PSU DTL

Reference CD player-transport top loading

Digidrive supply great read out hi precision the Cd-disc.

Magnetic and vibration phenomena was our first goal to reduce by design and practical solution.

Alluminium die cast chassis (2.5 mm thickness) supply hi-rigidity and no magnetics performance.

Separate power supply unit reduce influence of vibrations and magnetics flux.



Convenience & Optional

- SPDIF / AES-EBU XLR digital output connectors
- True-genuine top loading magnetic stabilizer
- Opto output digital by : 1) Toslink (basic solution) 2) ST-II laser (hi-quality solution [OPTIONAL])
- Original remote control handset
- Cherry wood veneered side panels
- Separate power supply unit
- Free genuine magnetics disc stabilizer

Design and hand-manufacture in middle Europe by:

Docet-Lector
Via Verdi,35
I-27010 Albuzzano (PV) Italy

tel: +++0382.484165
Fax +++0382.481021
Email: info@docet-lector.com
Web: www.docet-lector.com



Distributed by:



All about Digidrive TL

CARATTERISTICHE DEL Digidrive TL
ELECTRICAL PERFORMANCE OF Digidrive TL

ALL MEASUREMENT @ 1 KHz input reference CD-TEST CBS CD-1 @ 230 vac +/-5%

- Standard version off Digidrive TL

Type off unit	Integrated CD Player Transport top loading separate power supply
Digital outputs	SPDF by RCA connector, SPDF by BNC hi speed output, AES-EBU balanced RS 422
Reclocking	Internally generated XTAL precision only one oscillator for all function
Digital outputs optional	OPTO Toslink or OPTO ST-II bayonet
Power supply available PSU DTL	100 / 117 / 230 / 240 Vac 50/60 Hz 60 V/a
Dimension - external measurement of Digidrive TL	440 x 308 x 85 (L x P x H) mm Weight: 9 Kg net , 10.5 Kg. gross
Dimension-external measurement of PSU-DTL	200 x 308 x 85 (L x P x H) mm Weight: 5 Kg net , 6.0 Kg. gross
Accessories supply	Power cable mains / manual instruction/ Remote control handset / power supply unit PSU - DTL

- Version available of Digidrive TL

Digidrive + PSU DTL Standard Version	Basic version with three digital output only
Digidrive TL+ Toslink	With opto digital Toslink output
Digidrive TL+ ST II opto	With opto digital ST-II professional output

Note:

*Digidrive TL come supply as several version and is possible to add some outputs together.
Ex: Digidrive TL with Opto Toslink and ST-II opto professional*

Il Digidrive può essere fornito anche con l'aggiunta di più uscite.
Es: uscite digitali ottiche multiple: Toslink + ST-II