



Specification of Amplifier

MODEL	TYPE	PHONO	LINE AUX	DISTORS. % THD	POWER OUTPUT CH. RMS 8 OHM	FREQUENCY RESPONSE > 1 db	S/N RATIO	OUTPUTS CONNECTOR	SPEC'S DATA
VFI-50	LINE HYBRID INTEGRATED AMPLIFIER 5 LINE INPUT	NO INSIDE EXTERNAL MODULE MM70	200 mV 56Kohm 220 pf	0.1%	35 W.x 2	20-20 khz	95 db	PAIR SPEAKERS TAPE OUTPUT SPECIAL ON R	400 (L)x108 (H)x300(D) KG.8 NET 50-60 HZ 180 V/A 110/230 V-AC
VFI-70/L	LINE HYBRID INTEGRATED AMPLIFIER 4 LINE INPUT	NO INSIDE EXTERNAL MODULE MM70	150 mV	0.1%	40 W x 2	15-50 khz	95 db	PAIR SPEAKERS TAPE MONITOR SPECIAL ON R	400 (L)x100 (H)x300 (D) KG. 9 NET 50-60 HZ 200 V/A 110/230 V-AC
VFI-70/MM	PHONO MM LINE IN (3) INTEGRATED AMPLIFIER	1.8 mV 47 Kohm	220 mV	0.1%	40 W x 2	15-50 khz	95 db	PAIR SPEAKERS TAPE MONITOR SPECIAL ON R	400 (L)x100 (H)x300 (D) KG.9.2 NET 50-60 HZ 200 V/A 110/230 V-AC
VFI-70/MC	PHONO MC/MM LINE IN (3) INTEGRATED AMPLIFIER	0.4 mV (mc) 150 ohm 1.8 mV (mm) 47 kohm	220 mV	0.1%	40 W x 2	15-50 khz	95 db	PAIR SPEAKERS TAPE MONITOR SPECIAL ON R	400 (L)x100 (H)x300 (D) KG.9.2 NET 50-60 HZ 200 V/A 100/230 V-AC
VM-150	POWER AMPLIFIER	NOT AVAILABLE	1.2 volt 56 kohm 100 pf	0.1%	70 W x 2	15-50 khz	100 db	PAIR SPEAKERS BINDING POST	400 (L)x108 (H)x300 (D) KG.13 NET 50-60 HZ 300 V/A 100/230 V-AC
<i>ALL UNIT MEET CE-EMC- LVD REGULATION</i>									